

SF₆ Leak Detector 3-033-R002



Description:

An advanced microprocessor is the heart of this unit. Its Digital Signal Processing permits better management of the circuitry and sensing tip signal than ever before possible. Additionally, the number of components used in the circuit is reduced nearly 40%, increasing reliability and performance when searching for SF₆ leaks. The microprocessor monitors the sensing tip and battery voltage levels 2000 times per second, compensating for even the most minor fluctuations

in signal. This translates into a stable and dependable tool in almost any environment.

Convenience features have been added to enhance the usability of the 3-033-R002. Seven levels of sensitivity provide an increase of 64 times from level 1 to level 7. Unique Tri-Color LED's show a progressive and wide ranging leak size indication, communicate the sensitivity level, and provide a true voltage indication of battery power level.

A tactile keypad controls all functions of operation. A revolutionary new case design gives the user grip and control, and places the visual indicators in direct sight during use.



Features:

- Microprocessor control, with Advanced Digital Signal Processing
- Tricolor visual display of SF₆ leak intensity
- Seven (7) levels of sensitivity provide an increase of up to 64x
- Tactile keypad controls
- Real-time SF₆ sensitivity adjustment
- Battery test function
- Battery voltage indication
- True mechanical pumping provides positive airflow through sensing tip
- Mute feature included
- Cordless and portable
- Carrying case included
- 14" (35.5cm) flexible, stainless probe
- Optional carrying holster
- Three Year Warranty

Power Supply: 3V DC; two "C" cell Alkaline batteries
Maximum Sensitivity: SF₆ @ 0.5 oz/yr. (14gr/yr)
Operating Temperature: 30° to 125° F (0° to 52° C)
Battery Life: Approximately 30 hours normal use
Duty Cycle: Continuous, no limitation
Response Time: Instantaneous
Reset Time: One second
Warm-Up Time: Approximately 2 Seconds
Unit Weight: 1.2 lbs (560 grams)
Unit Dimensions: 9" x 2.5" x 2.5"
(22.9 cm x 6.5cm x 6.5cm)
Fixed Probe Length: 14" (35.5 cm)